Supplier's name or trade mark Vortice Specific Energy Consumption class SEC in average climate zone n.0.0 Specific Energy Consumption class SEC average [kWh/m2a] -23.4 Specific Energy Consumption class SEC cold [kWh/m2a] -24.4 Specific Energy Consumption class SEC warm [kWh/m2a] -24.4 Declared typology UVR-U: unidirezionale Type of drive NA Type of heat recovery system HRS assente Thermal efficiency of heat recovery at reference air flow [%] NA Maximum flow rate [m3/h] 311 Electric power input of the fan drive, including any motor control equipment, at maximum flow rate [m3/s) 69.6 Sund power level LWA [dB(A)] 69.6 Reference flow rate [m3/s] 10,0605 Reference pressure difference [Pa] 10 SPI [W/(m3/h)] 1 Control factor CTRL 1 Control factor CTRL 1 Maximum external leakage rates [%] NA Mixing rate NA Position and description of visual filter warning NA Airflow sensitivity to pressure variations at +20Pa and -20 Pa NA	ATTRIBUTO	VALORE ATTRIBUTO
Specific Energy Consumption class SEC average [kWh/m2a] -10,0 Specific Energy Consumption class SEC cold [kWh/m2a] -23,4 Specific Energy Consumption class SEC warm [kWh/m2a] -2,4 Declared typology UVR-U: unidirezionale Type of drive NA Type of heat recovery system HRS assente Thermal efficiency of heat recovery at reference air flow [%] NA Maximum flow rate [m3/h] 311 Electric power input of the fan drive, including any motor control equipment, at maximum flow rate [W] 25,0 Sound power level LWA [dB(A)] 69 Reference flow rate [m3/s] 0,0605 Reference pressure difference [Pa] 30 SPI [W/(m3/h)] 0,11484 Control factor CTRL 1 Control typology manuale Maximum internal leakage rates [%] NA Maximum external leakage rates [%] NA Mixing rate NA Position and description of visual filter warning NA Airflow sensitivity to pressure variations at + 20Pa and - 20 Pa NA Indoor/outdoor air tightness [m3/h] NA Annua	Supplier's name or trade mark	Vortice
Specific Energy Consumption class SEC cold [kWh/m2a]-23,4Specific Energy Consumption class SEC warm [kWh/m2a]-2,4Declared typologyUVR-U: unidirezionaleType of driveNAType of heat recovery system HRSassenteThermal efficiency of heat recovery at reference air flow [%]NAMaximum flow rate [m3/h]311Electric power input of the fan drive, including any motor control equipment, at maximum flow rate [W]5,0Sound power level LWA [dB(A)]69Reference flow rate [m3/s]0,0605Reference pressure difference [Pa]30SPI [W/(m3/h)]1,1184Control factor CTRL1Control factor CTRL1Control factor LypologymanualeMaximum internal leakage rates [%]NAMixing rateNAPosition and description of visual filter warningNAAirflow sensitivity to pressure variations at + 20Pa and – 20 PaNAAnnual electricity consumption (AEC) [kWh electricity/a]158AHS average Annual heating saved [kWh primary energy/a]1397	Specific Energy Consumption class SEC in average climate zone	NA
Specific Energy Consumption class SEC warm [kWh/m2a]2,4Declared typologyUVR-U unidirezionaleType of driveNAType of florivesasenteType of heat recovery system HRSNAMaximum flow rate [m3/h]311Electric power input of the fan drive, including any motor control equipment, at maximum flow rate [W]25,0Sound power level LWA [dB(A)]69Reference flow rate [m3/s]0,0605Reference pressure difference [Pa]30SPI [W/(m3/h)]0,11484Control factor CTRL1Control factor CTRLNAMaximum internal leakage rates [%]NAMaximum external leakage rates [%]NAMixing rateNAPosition and description of visual filter warningNAAirflow sensitivity to pressure variations at + 20Pa and – 20 PaNAAnnual electricity consumption (AEC) [kWh electricity/a]158AHS average Annual heating saved [kWh primary energy/a]1397AHS cold Annual heating saved [kWh primary energy/a]2732	Specific Energy Consumption class SEC average [kWh/m2a]	-10,0
Declared typology Type of drive NA Type of heat recovery system HRS Type of heat recovery system HRS NA Maximum flow rate [m3/h] Electric power input of the fan drive, including any motor control equipment, at maximum flow rate [W] Sound power level LWA [dB(A)] Reference flow rate [m3/s] Reference pressure difference [Pa] SPI [W/(m3/h)] Control factor CTRL Control factor CTRL Control factor CTRL Awaimum internal leakage rates [%] Maximum external leakage rates [%] Mixing rate Position and description of visual filter warning Airflow sensitivity to pressure variations at + 20Pa and – 20 Pa Alfaloor/outdoor air tightness [m3/h] Alfalor average Annual heating saved [kWh primary energy/a] Alfs odd Annual heating saved [kWh primary energy/a] Alfs cold Annual heating saved [kWh primary energy/a] Alfs cold Annual heating saved [kWh primary energy/a] Alfs cold Annual heating saved [kWh primary energy/a]	Specific Energy Consumption class SEC cold [kWh/m2a]	-23,4
Type of drive NA Service of drive Assert of the trecovery system HRS asserte Thermal efficiency of heat recovery at reference air flow [%] NA Assert of heat recovery at reference air flow [%] NA Assert of heat recovery at reference air flow [%] NA Assert of heat recovery at reference air flow [%] NA Assert of heat recovery at reference air flow [%] NA Assert of heat recovery at reference air flow [%] NA Assert of heat recovery at reference air flow [%] NA Assert of heat recovery at reference air flow [%] NA Assert of heat recovery at reference air flow [%] NA Assert of heat recovery at reference air flow [%] NA Assert of heat recovery at reference air flow [%] NA Assert of heat recovery at reference air flow [%] NA Assert of heat recovery at reference air flow [%] NA Assert of heat recovery at reference air flow [%] NA Assert of heat recovery at reference air flow [%] NA Assert of heat recovery at reference air flow [%] NA Assert of heat recovery at reference air flow [%] NA Annual electricity to pressure variations at + 20Pa and – 20 Pa NA Annual electricity consumption (AEC) [kWh electricity/a] NA Annual electricity consumption (AEC) [kWh electricity/a] NA Annual heating saved [kWh primary energy/a] NA Secold Annual heating saved [kWh primary energy/a]	Specific Energy Consumption class SEC warm [kWh/m2a]	-2,4
Type of heat recovery system HRS Thermal efficiency of heat recovery at reference air flow [%] Maximum flow rate [m3/h] Electric power input of the fan drive, including any motor control equipment, at maximum flow rate [W] Sound power level LWA [dB(A)] Reference flow rate [m3/s] Reference pressure difference [Pa] SPI [W/(m3/h)] Control factor CTRL Control factor CTRL Control typology Maximum internal leakage rates [%] Maximum external leakage rates [%] Mixing rate NA Mixing rate NA Airflow sensitivity to pressure variations at + 20Pa and – 20 Pa Annual electricity consumption (AEC) [kWh electricity/a] AHS overage Annual heating saved [kWh primary energy/a] AHS cold Annual heating saved [kWh primary energy/a] Asserting a saved fixed and a sensitivity to pressure at recovery at reference air flow [%] NA Asserting the saved [kWh primary energy/a] AHS cold Annual heating saved [kWh primary energy/a] Asserting the saved fixed primary energy/a]	Declared typology	UVR-U: unidirezionale
Thermal efficiency of heat recovery at reference air flow [%]NAMaximum flow rate [m3/h]311Electric power input of the fan drive, including any motor control equipment, at maximum flow rate [W]25,0Sound power level LWA [dB(A)]69Reference flow rate [m3/s]0,0605Reference pressure difference [Pa]30SPI [W/(m3/h)]0,11484Control factor CTRL1Control typologymanualeMaximum internal leakage rates [%]NAMixing rateNAPosition and description of visual filter warningNAAirflow sensitivity to pressure variations at + 20Pa and – 20 PaNAAnnual electricity consumption (AEC) [kWh electricity/a]158AHS average Annual heating saved [kWh primary energy/a]2732	Type of drive	NA
Maximum flow rate [m3/h] 311 Electric power input of the fan drive, including any motor control equipment, at maximum flow rate [W] 25,0 Sound power level LWA [dB(A)] 69 Reference flow rate [m3/s] 0,0605 Reference pressure difference [Pa] 30 SPI [W/(m3/h)] 0,11484 Control factor CTRL 1 Control typology manuale Maximum internal leakage rates [%] NA Maximum external leakage rates [%] NA Mixing rate NA Position and description of visual filter warning NA Airflow sensitivity to pressure variations at + 20Pa and – 20 Pa Indoor/outdoor air tightness [m3/h] NA Annual electricity consumption (AEC) [kWh electricity/a] 158 AHS average Annual heating saved [kWh primary energy/a] 2732	Type of heat recovery system HRS	assente
Electric power input of the fan drive, including any motor control equipment, at maximum flow rate [W] 5.0 Sound power level LWA [dB(A)] 69 Reference flow rate [m3/s] 0,0605 Reference pressure difference [Pa] 30 SPI [W/(m3/h)] 0,11484 Control factor CTRL 1 Control typology manuale Maximum internal leakage rates [%] NA Maximum external leakage rates [%] NA Mixing rate NA Position and description of visual filter warning NA Airflow sensitivity to pressure variations at + 20Pa and – 20 Pa Indoor/outdoor air tightness [m3/h] NA Annual electricity consumption (AEC) [kWh electricity/a] 158 AHS average Annual heating saved [kWh primary energy/a] 1397 AHS cold Annual heating saved [kWh primary energy/a] 2732	Thermal efficiency of heat recovery at reference air flow [%]	NA
Sound power level LWA [dB(A)] Reference flow rate [m3/s] Reference pressure difference [Pa] 30 SPI [W/(m3/h)] Control factor CTRL 1 Control typology manuale Maximum internal leakage rates [%] MA Maximum external leakage rates [%] MA Mixing rate NA Position and description of visual filter warning Airflow sensitivity to pressure variations at + 20Pa and – 20 Pa Indoor/outdoor air tightness [m3/h] Annual electricity consumption (AEC) [kWh electricity/a] AHS average Annual heating saved [kWh primary energy/a] AHS cold Annual heating saved [kWh primary energy/a] AHS cold Annual heating saved [kWh primary energy/a] 70 80 80 80 80 80 80 80 80 80 80 80 80 80	Maximum flow rate [m3/h]	311
Reference flow rate [m3/s] 0,0605 Reference pressure difference [Pa] 30 SPI [W/(m3/h)] 0,11484 Control factor CTRL 1 Control typology manuale Maximum internal leakage rates [%] NA Maximum external leakage rates [%] NA Mixing rate NA Position and description of visual filter warning NA Airflow sensitivity to pressure variations at + 20Pa and – 20 Pa Indoor/outdoor air tightness [m3/h] NA Annual electricity consumption (AEC) [kWh electricity/a] 158 AHS average Annual heating saved [kWh primary energy/a] 2732	Electric power input of the fan drive, including any motor control equipment, at maximum flow rate [W]	25,0
Reference pressure difference [Pa] 30 SPI [W/(m3/h)] 0,11484 Control factor CTRL 1 Control typology manuale Maximum internal leakage rates [%] NA Maximum external leakage rates [%] NA Mixing rate NA Position and description of visual filter warning NA Airflow sensitivity to pressure variations at + 20Pa and – 20 Pa Indoor/outdoor air tightness [m3/h] NA Annual electricity consumption (AEC) [kWh electricity/a] 158 AHS average Annual heating saved [kWh primary energy/a] 2732	Sound power level LWA [dB(A)]	69
SPI [W/(m3/h)] 0,11484 Control factor CTRL 1 Control typology manuale Maximum internal leakage rates [%] NA Maximum external leakage rates [%] NA Mixing rate NA Position and description of visual filter warning NA Airflow sensitivity to pressure variations at + 20Pa and – 20 Pa Indoor/outdoor air tightness [m3/h] NA Annual electricity consumption (AEC) [kWh electricity/a] 158 AHS average Annual heating saved [kWh primary energy/a] 1397 AHS cold Annual heating saved [kWh primary energy/a] 2732	Reference flow rate [m3/s]	0,0605
Control factor CTRL 1000 1000 1000 1000 1000 1000 1000 10	Reference pressure difference [Pa]	30
Control typology manuale Maximum internal leakage rates [%] NA Maximum external leakage rates [%] NA Mixing rate NA Position and description of visual filter warning NA Airflow sensitivity to pressure variations at + 20Pa and – 20 Pa Indoor/outdoor air tightness [m3/h] NA Annual electricity consumption (AEC) [kWh electricity/a] 158 AHS average Annual heating saved [kWh primary energy/a] 1397 AHS cold Annual heating saved [kWh primary energy/a] 2732	SPI [W/(m3/h)]	0,11484
Maximum internal leakage rates [%] Maximum external leakage rates [%] Mixing rate NA Position and description of visual filter warning Airflow sensitivity to pressure variations at + 20Pa and – 20 Pa Indoor/outdoor air tightness [m3/h] Annual electricity consumption (AEC) [kWh electricity/a] AHS average Annual heating saved [kWh primary energy/a] AHS cold Annual heating saved [kWh primary energy/a] NA 2732	Control factor CTRL	1
Maximum external leakage rates [%] Mixing rate Position and description of visual filter warning Airflow sensitivity to pressure variations at + 20Pa and – 20 Pa Indoor/outdoor air tightness [m3/h] Annual electricity consumption (AEC) [kWh electricity/a] AHS average Annual heating saved [kWh primary energy/a] AHS cold Annual heating saved [kWh primary energy/a] AHS cold Annual heating saved [kWh primary energy/a]	Control typology	manuale
Mixing rate Position and description of visual filter warning Airflow sensitivity to pressure variations at + 20Pa and – 20 Pa Indoor/outdoor air tightness [m3/h] Annual electricity consumption (AEC) [kWh electricity/a] AHS average Annual heating saved [kWh primary energy/a] AHS cold Annual heating saved [kWh primary energy/a] AHS cold Annual heating saved [kWh primary energy/a]	Maximum internal leakage rates [%]	NA
Position and description of visual filter warning Airflow sensitivity to pressure variations at + 20Pa and – 20 Pa Indoor/outdoor air tightness [m3/h] Annual electricity consumption (AEC) [kWh electricity/a] AHS average Annual heating saved [kWh primary energy/a] AHS cold Annual heating saved [kWh primary energy/a] 2732	Maximum external leakage rates [%]	NA
Airflow sensitivity to pressure variations at + 20Pa and – 20 Pa Indoor/outdoor air tightness [m3/h] Annual electricity consumption (AEC) [kWh electricity/a] AHS average Annual heating saved [kWh primary energy/a] AHS cold Annual heating saved [kWh primary energy/a] 2732	Mixing rate	NA
Indoor/outdoor air tightness [m3/h] Annual electricity consumption (AEC) [kWh electricity/a] AHS average Annual heating saved [kWh primary energy/a] AHS cold Annual heating saved [kWh primary energy/a] 2732	Position and description of visual filter warning	NA
Annual electricity consumption (AEC) [kWh electricity/a] 158 AHS average Annual heating saved [kWh primary energy/a] 1397 AHS cold Annual heating saved [kWh primary energy/a] 2732	Airflow sensitivity to pressure variations at + 20Pa and – 20 Pa	NA
AHS average Annual heating saved [kWh primary energy/a] 1397 AHS cold Annual heating saved [kWh primary energy/a] 2732	Indoor/outdoor air tightness [m3/h]	NA
AHS cold Annual heating saved [kWh primary energy/a] 2732	Annual electricity consumption (AEC) [kWh electricity/a]	158
	AHS average Annual heating saved [kWh primary energy/a]	1397
AHS warm Annual heating saved [kWh primary energy/a] 632	AHS cold Annual heating saved [kWh primary energy/a]	2732
	AHS warm Annual heating saved [kWh primary energy/a]	632